

Soft Flex

Royalty Bracelet

Designed by: **Jamie Hogsett**

Skill Level: **Beginner**

Beads available from:
FusionBeads.com

Finished Size: **7 3/4"**

Materials

20 Gauge Purple Soft Flex® Craft Wire

20 Gauge Peacock Soft Flex® Craft Wire

20 Gauge Black Soft Flex® Craft Wire

25mm x 31mm purple glass and sterling silver
box clasp - 1 clasp set

14mm x 9mm tanzanite flat oval Czech
lampwork bead - 4 ovals

11mm tanzanite square Czech
lampwork bead - 4 squares

6mm cardinal purple fire-polished rounds - 10 rounds

3mm black diamond Swarovski Elements crystal
flat back rhinestones - 2 flat backs

GS Hypo-Cement

Tools

Tweezers

Cutters

Chain Nose Pliers

Round Nose Pliers

Flat Nose Pliers

Instructions

Step 1: Place a small dot of hypo-cement on the center of 1 square. Use tweezers to place a rhinestone on the dot of hypo-cement. Repeat to place the second rhinestone on a second square. Let dry.

Step 2: Use 2" of purple wire to form a wire-wrapped loop. String 1 fire-polished round and form a wrapped loop. Repeat entire step seven times for a total of eight round links.

Step 3: Use 2 1/2" of peacock wire to form a wire-wrapped loop that attaches to 1 round link. String 1 square from Step 1. Form a wire-wrapped loop that attaches to 1 round link.

Step 4: Use 2 1/2" of black wire to form a wire-wrapped loop that attaches to the other side of the previous link. String 1 oval. Form a wire-wrapped loop that attaches to 1 round link.



Soft Flex

Royalty Bracelet

Finished Size: 7 3/4"



Instructions Continued:

Step 5: Use 2 1/2" of peacock wire to form a wire-wrapped loop that attaches to the other side of the previous link. String 1 square. Form a wire-wrapped loop that attaches to 1 round link.

Step 6: Use 2 1/2" of black wire to form a wire-wrapped loop that attaches to the other side of the previous link. String 1 oval. Form a wire-wrapped loop. Set chain aside.

Step 7: Use 2 1/2" of black wire to form a wire-wrapped loop that attaches to 1 round link. String 1 square. Form a wire-wrapped loop that attaches to 1 round link.

Step 8: Use 2 1/2" of peacock wire to form a wire-wrapped loop that attaches to the other side of the previous link. String 1 oval. Form a wire-wrapped loop that attaches to 1 round link.

Step 9: Use 2 1/2" of black wire to form a wire-wrapped loop that attaches to 1 round link. String 1 square from Step 1. Form a wire-wrapped loop that attaches to 1 round link.

Step 10: Use 2 1/2" of peacock wire to form a wire-wrapped loop that attaches to the other side of the previous link. String 1 oval. Form a wire-wrapped loop.

Step 11: Use 2" of purple wire to form a wire-wrapped loop that attaches to the open purple loop of the chain set aside in Step 6 and the open peacock loop of the chain finished in Step 10. String 1 fire-polished round. Form a wire-wrapped loop that attaches to one half of the clasp.

Step 12: Use 2" of purple wire to form a wire wrapped loop that attaches to the other two chain ends. String 1 fire-polished round. Form a wire-wrapped loop that attaches to the other half of the clasp.



Projects not intended for children under the age of 13.

The information on this instruction sheet is presented in good faith, but no warranty is given, nor results guaranteed.

Soft Flex® Company disclaims all liability from any injury to anyone undertaking the construction of this project as a result of improper safety precautions.